

**ELECTRIC DRYER DEL-2499A**

**60 cm belt width, heat chamber 250cm**

**Machine**

<b>1</b>	Total length	350 cm		
<b>2</b>	Heat chamber length	250 cm		
<b>3</b>	Belt width	60 cm		
<b>4</b>	Inlet / outlet length	50 cm		
<b>5</b>	High	115 cm		
<b>6</b>	Electrical requirements	400V, 3PH, 10.5 kW, 32A CEE-plug		
<b>7</b>	Belt rotation direction	Both side ( left & right )		
<b>8</b>	Belt drive	frequency converter, sleeplessly adjustable		
<b>9</b>	Belt type	fiberglass Teflon coated, 4x4 mm mesh-size		
<b>10</b>	Exhaust connection	100 mm		
<b>11</b>	Heating elements	3.3 um IR wave length		
<b>12</b>	Temperature control	PID		
<b>13</b>	Cool skin technology	150 mm insulation 4 walls		
<b>14</b>	If equipped with Hot air circulation cures wide range of inks with all substrates (also paper and plastic)	Plastisol Inks	Water base Inks	Solvent Inks
<b>15</b>	Guarantee	2 years limited warranty		
<b>16</b>	Production capacity (curing element size 40 x 50 cm, curing conditions 1 min in 160°C)	360 pcs/hr		
<b>MACHINE EQUIPMENT IN OPTION</b>				
<b>17</b>	Wheels option per 1 oven	YES	1	
<b>18</b>	Hot air circulation* per 1 oven ( 1300 m <sup>3</sup> /h )	NO	1	
<b>19</b>	Cooling System	NO	0	