

GAS DRYING TUNNEL GAL-60146

MACHINE

| | | | | |
|-----------|-------------------------|---|-------------------------|-------------------------|
| 1 | Total length | 614 cm | | |
| 2 | Heat chamber length | 370 cm | | |
| 3 | Belt width | 152 cm | | |
| 4 | Inlet / outlet length | 120 cm | | |
| 6 | High | 130 cm | | |
| 7 | Electrical requirements | 400V, 3PH, 3 kW, 32A CEE-plug | | |
| 8 | Belt rotation direction | Both side(left & right) | | |
| 9 | Belt drive | frequency converter, sleeplessly adjustable 1 – 5 m/min | | |
| 10 | Belt type | fiberglass Teflon coated, 4x4 mm mesh-size | | |
| 11 | Exhaust connection | 150 cm | | |
| 12 | Heating elements | GAS BURNER, HEAT EXCHANGER, HOT AIR FREE OF FUMES | | |
| 13 | GAS BURNER TYPE | min power 20 kW | max power 70 kW | |
| 14 | GAS Consumption | AVERAGE at 180°C 4,2 litres/h | Min 2,1 litres/h | Max 7,3 litres/h |
| 15 | Hot air circulation | INCLUDED | | |
| 16 | Temperature control | PID | | |
| 17 | Light tower | Signalize STAGES OF MACHINE | | |
| 18 | Warranty | 2 years limited warranty | | |