

WORKMAN 8 stations / 6 colors		DESCRIPTION			
	Machine				
1	Total diameter	300 cm			
2	Base diameter	118 cm			
3	Total weight	1400 kg			
4	High	160 cm			
5	Air consumption / pressure	550 l/min, 6 bar(90psi)			
6	Electrical requirements	230V, 1PH, 60W, 1A			
7	Max PRINT area	16" x 16"			
8	Direction	one side(CCW)			
9	Max print speed	900 cycle/hour			
10	Squeegee & Flood speed	Independent for each printing head			
11	Warranty	2 years limited warranty			
12	Multi print	Multiple print for chosen print head			
13	Multi print TABLE UP / DOWN	Choice for UP or DOWN TABLE position between MULTI PRINT STROKES			
14	Test print	Possibility to run press in test print mode for individual print head or for all colors			
15	Free wheel	Possibility to unlock indexer to move lower wheel with table by hand			
16	Max Screen Size	Size 56x71 cm			
17	Programing machine cycle	Possibility to program for special sequence printing system			
MACHINE EQUIPMENT IN STANDARD					
18	Pneumatic INDEX	Precision rotation system	1		INCLUDED
19	Pneumatic Print Heads	Driven by pneumatic pistons, with speed control in both directions	6		INCLUDED
20	Pneumatic lift	Pneumatic cylinder 4"	1		INCLUDED
21	Central OFF Contact	Manual off-contact change	1		INCLUDED
22	Screen AIR locking / per head	Four pneumatic cylinder per screen, manually switched	6		INCLUDED
23	Skip Switch	On the control panel	1		INCLUDED
24	Quick change Slide Mount platen system	Easy & fast to change platens	8		INCLUDED
25	Pneumatic fasten Squeegee & Flood	Pneumatic system to realize SQ & FL fasten	N/A		N/A
26	Foot Pedal	Let you to control the press	Option		OPTION
27	Main air regulator with water filter, oil lubrication	Easy to control and service air pressure with oil tank to keep all pneumatic parts in good condition	1		INCLUDED
28	Measure indicator for print stroke	Easy to read and change print stroke length and position	6		INCLUDED
29	Side (left & right) screen holders	More accessible to put each size of screen onto screen holder	6		INCLUDED
30	Micro Adjustment	Very precision screen's micro registration	6		INCLUDED
31	Micro Dial Indicator	Simple indicator to see any adjustments	6		INCLUDED

32	Rotatable control panel	gives all head control access	1		INCLUDED
33	load and unload safety System	Electric safety bars protecting load and unload positions while machine's rotation	1 set		INCLUDED
34	Print head reduction	- € 600 for take off print head; additional head in the future cost 2600€	Choice		See below
35	1set FREE Squeegee/Flood	16 " length	1		INCLUDED
36	1set FREE Pallets	aluminum rubber coated; size 16" x 22 "	1		INCLUDED
M A C H I N E E Q U I P M E N T I N O P T I O N					
37	Pneumatic fasten Squeegee & Flood	+ €200 per print head			
38	1 set extra aluminum pallets cm	Aluminum rubber coated; size cm			
39	1 set extra squeegee with blade 70 durometer	The length cm			
40	1 set extra aluminum flood bar	The length cm			
41	Foot Pedal	Let you to control the press by foot switch			
42	Printing head reduction on the press	Reduction printing heads relation to standard size			
43	CPM-1618 ceramic panel heater	Ceramic panel heater with temperature control, 3 kW, 16A, 230 V			
44	CPM-1618-C ceramic panel heater	Ceramic panel heater with temperature control and air flow, 8 kW, 16A, 400 V			
45	Flash holder for QLH/CLH if head is missing	Special head to put flash cure on the press			
46	IR Carbon Quartz Flash CLH 1618	Quartz heater, heat area 16 x 18", Electronic power control, pallet temperature sensor, temperature setting and reading max power 12 kW (auto or manual control)			
47	IR Quartz Flash QLH 1618	Quartz Infrared heater, heat area 16 x 18", Electronic power control, max power 12 kW (auto or manual control)			

